



# EURO G

Article: **41070 GR**

Unipolar distribution terminal block – screw system  
 – 15 holes – 1,5mm<sup>2</sup> / 10 mm<sup>2</sup> – 63A - 500V – green



## GENERAL INFORMATION

Series	<b>EURO G</b>
Item	<b>41070 GR</b>
Weight/Piece	<b>57.6 g.</b>
Customs tariff	<b>85369010</b>
Catalog	<b>01</b>
Colour	green
Q.ty p.pck.	<b>10</b>
Q.ty p. box	<b>250</b>

## TECHNICAL DATA / DIMENSIONS

### Dimensions

Width (C) mm	20
Length (A) mm	113
Height (B) mm	34
Mounting type (EN 60715)	Omega TH35
Mounting type	panel mounting by means of the hole on the bottom of the base

### Technical data

Type of connection	Screw system
Screw	Zinc plated still
Tightening torque	2Nm
Holes number	15
Holes diameter	Ø 5,3mm
Current bar	Brass CW614N
Insulating material	PA
Self-extinguishing degree acc. to UL94	V2
Rated surge voltage	8kV
Rated current	63A
Rated voltage	500V
Heat resistance	130°C

### Connection data

Rated connection –MIN.	1,5 mm <sup>2</sup>
Rated connection –MAX.	10 mm <sup>2</sup>



STANDARDS

**EN60947-7-1**      10mm<sup>2</sup> – 500V – 63A

TECHNICAL DRAWINGS

