


FKL5521

Color RAL7035/RAL7032 IP rating IP54/55

Max airflow: **76m³/h**
Dimensions(WxH): 111.2x111.2mm




Model	FKL5521-8025.230	FKL5521.115	FKL5521.024
Order number	2025.049/2025.050	2025.023/2025.047	2025.024/2025.048
Fan model	F2E-8025B-230	F2E-8025B-115	F2E-8025B-24
Rated voltage (V / Hz)	230/50/60	115/50/60	24(DC)
Air flow	IP20	30/36m ³ /h	76m ³ /h
	IP54	20/25m ³ /h	40m ³ /h
Motor type	Shaded-Pole Motor		DC Motor
Rated current (A)	0.08/0.07	0.14/0.16	0.13
Power (W)	15/12	10/12	3.10
Noise level (dB)	36/38		34
Operating temperature range	-10°C to +55°C		
Exit filter	FKL5521.300 RAL7035 / RAL7032 (2025.021 / 2025.045)		

FKL5522

Color RAL7035/RAL7032 IP rating IP54/55

Max airflow: **195m³/h**
Dimensions(WxH): 145.2x145.2mm




Model	FKL5522.230	FKL5522.115	FKL5522.024
Order number	2025.001/2025.025	2025.002/2025.026	2025.003/2025.027
Fan model	F2E-120S-230	F2E-120S-115	F2E-120B-24
Rated voltage (V / Hz)	230/50/60	115/50/60	24(DC)
Air flow	IP20	145/160m ³ /h	195m ³ /h
	IP54	72/75m ³ /h	80m ³ /h
Motor type	Shaded-Pole Motor		DC Motor
Rated current (A)	0.12/0.10	0.34/0.28	0.40
Power (W)	20/15	25/21	9.60
Noise level (dB)	50/52		
Operating temperature range	-10°C to +55°C		
Exit filter	FKL5522.300 RAL7035 / RAL7032 (2025.004 / 2025.028)		

FKL5523

Color RAL7035/RAL7032 IP rating IP54/55

Max airflow: **195m³/h**
Dimensions(WxH): 250x250mm




Model	FKL5523.230	FKL5523.115	FKL5523.024
Order number	2025.005/2025.029	2025.006/2025.030	2025.007/2025.031
Fan model	F2E-120S-230	F2E-120S-115	F2E-120B-24
Rated voltage (V / Hz)	230/50/60	115/50/60	24(DC)
Air flow	IP20	145/160m ³ /h	195m ³ /h
	IP54	100/103m ³ /h	80m ³ /h
Motor type	Shaded-Pole Motor		DC Motor
Rated current (A)	0.12/0.10	0.34/0.28	0.40
Power (W)	20/15	25/21	9.60
Noise level (dB)	50/52		
Operating temperature range	-10°C to +55°C		
Exit filter	FKL5523.300 RAL7035 / RAL7032 (2025.008 / 2025.032)		

FKL5525-150

Color RAL7035/RAL7032 IP rating IP54/55

Max airflow: **370m³/h**
Dimensions(WxH): 250x250mm




Model	FKL5525-150.230	FKL5525-150.115
Order number	2025.009/2025.033	2025.010/2025.034
Fan model	F2E-150S-230	F2E-150S-115
Rated voltage (V / Hz)	230/50/60	115/50/60
Air flow	IP20	370/325m ³ /h
	IP54	230/200m ³ /h
Motor type	Shaded-Pole Motor	
Rated current (A)	0.29/0.27	0.61/0.54
Power (W)	43/40	44/41
Noise level (dB)	58	
Operating temperature range	-10°C to +55°C	
Exit filter	FKL5525.300 RAL7035 / RAL7032 (2025.008 / 2025.032)	

FKL5525-162

Max airflow: **380m³/h**
Dimensions(WxH): 250x250mm

Color: RAL7035/RAL7032
IP rating: IP54/55




Model	FKL5525-162.230	FKL5525-162.115	FKL5525-162.024
Order number	2025.012/2025.036	2025.013/2025.037	2025.011/2025.035
Fan model	F2E-162B-230	F2E-162B-115	F2E-162B-24
Rated voltage (V / Hz)	230/50/60	115/50/60	24(DC)
Air flow	IP20	325/380m ³ /h	
	IP54	200/235m ³ /h	
Motor type	Shaded-Pole Motor		DC Motor
Rated current (A)	0.23/0.20	0.53/0.41	0.46
Power (W)	37/36	36/34	11.04
Noise level (dB)	48/53		
Operating temperature range	-10°C to +55°C		
Exit filter	FKL5525.300 RAL7035 / RAL7032 (2025.008 / 2025.032)		

FKL5525-200

Max airflow: **680m³/h**
Dimensions(WxH): 250x250mm

Color: RAL7035/RAL7032
IP rating: IP54/55




Model	FKL5525-200.230	FKL5525-200.115
Order number	2025.014/2025.038	2025.015/2025.039
Fan model	F2E-200B-230	F2E-200B-115
Rated voltage (V / Hz)	230/50/60	115/50/60
Air flow	IP20	680m ³ /h
	IP54	420/450m ³ /h
Motor type	Shaded-Pole Motor	
Rated current (A)	0.36/0.40	0.70/0.83
Power (W)	50/53	50/53
Noise level (dB)	63/67	
Operating temperature range	-10°C to +55°C	
Exit filter	FKL5525.300 RAL7035 / RAL7032 (2025.008 / 2025.032)	

FKL5526

Max airflow: **1050m³/h**
Dimensions(WxH): 320x320mm

Color: RAL7035/RAL7032
IP rating: IP54/55




Model	FKL5526.230	FKL5526.115
Order number	2025.016/2025.040	2025.017/2025.041
Fan model	F2E-260B-230	F2E-260B-115
Rated voltage (V / Hz)	230/50/60	115/50/60
Air flow	IP20	925/1050m ³ /h
	IP54	450/500m ³ /h
Motor type	Shaded-Pole Motor	
Rated current (A)	0.32/0.30	0.58/0.60
Power (W)	64/71	67/74
Noise level (dB)	62/64	
Operating temperature range	-10°C to +55°C	
Exit filter	FKL5526.300 RAL7035 / RAL7032 (2025.020 / 2025.044)	

FKL5526-D

Max airflow: **1800m³/h**
Dimensions(WxH): 320x320mm

Color: RAL7035/RAL7032
IP rating: IP54/55



Model	FKL5526.230-D	FKL5526.115-D
Order number	2025.018/2025.042	2025.019/2025.043
Fan model	F2E-320B-230	F2E-320B-115
Rated voltage (V / Hz)	230/50/60	115/50/60
Air flow	IP20	1720/1800m ³ /h
	IP54	1038/1056m ³ /h
Motor type	Shaded-Pole Motor	
Rated current (A)	0.50/0.70	1.00/1.20
Power (W)	119/153	105/125
Noise level (dB)	68/70	
Operating temperature range	-10°C to +55°C	
Exit filter	FKL5526.300 RAL7035 / RAL7032 (2025.020 / 2025.044)	