



## ENCLOSURES SERIES OK / AF/AS

### DTE – Glazed door

**Description:** the glazed doors are used on the OK series, as well as on the mooblock AS and AF series. They are made up of metal steel sheet thick 2.0 mm and have a wide plate of polymethyl metacrylate (PMMA) thick 4.0 mm, in conformity with DIN, ASTM and ISO norms. The transparent plate is fixed to the door by a double adhesive closed cell acrylic film, resistant to high temperature and impacts. The plate fixing is reinforced by galvanised brackets installed on the door inner frame. For all other characteristics please refer to (page 18).

#### DTE code includes:

- Glazed door, metal sheet painted RAL7035 textured, transparent plate and inner stiffening frame with corner pieces in zama
- Set of 4 standard hinges 120° CAP120 (pag. 178)
- Set of 4 latches NTL999 (pag. 177)
- Standard locking, espanolette system, double bar 3mm
- Screws and gaskets

**Notes:** doors H=1200 and 1400 are available for enclosures AF and AS series.  
- available hinges 180° opening

CODE	Nominal dimensions		Other dimensions					
	H	L	C	G	E	F	M	N
DTE126	1200	600	1184	592	1015	440	390	980
DTE128	1200	800	1184	792	1015	640	590	980
DTE12A	1200	1000	1184	992	1015	840	790	980
DTE12C	1200	1200	1184	592 <sup>(?)</sup>	1015	440 <sup>(?)</sup>	390 <sup>(?)</sup>	980
DTE146	1400	600	1384	592	1215	440	390	1180
DTE148	1400	800	1384	792	1215	640	590	1180
DTE14A	1400	1000	1384	992	1215	840	790	1180
DTE14C	1400	1200	1384	592 <sup>(?)</sup>	1215	440 <sup>(?)</sup>	390 <sup>(?)</sup>	1180
DTE166	1600	600	1584	592	1415	440	390	1380
DTE168	1600	800	1584	792	1415	640	590	1380
DTE16A	1600	1000	1584	992	1415	840	790	1380
DTE16C	1600	1200	1584	592 <sup>(?)</sup>	1415	440 <sup>(?)</sup>	390 <sup>(?)</sup>	1380
DTE186	1800	600	1784	592	1615	440	390	1580
DTE188	1800	800	1784	792	1615	640	590	1580
DTE18A	1800	1000	1784	992	1615	840	790	1580
DTE18C	1800	1200	1784	592 <sup>(?)</sup>	1615	440 <sup>(?)</sup>	390 <sup>(?)</sup>	1580
DTE18E	1800	1600	1784	792 <sup>(?)</sup>	1615	640 <sup>(?)</sup>	590 <sup>(?)</sup>	1580
DTE206	2000	600	1984	592	1815	440	390	1780
DTE208	2000	800	1984	792	1815	640	590	1780
DTE20A	2000	1000	1984	992	1815	840	790	1780
DTE20C	2000	1200	1984	592 <sup>(?)</sup>	1815	440 <sup>(?)</sup>	390 <sup>(?)</sup>	1780
DTE20E	2000	1600	1984	792 <sup>(?)</sup>	1815	640 <sup>(?)</sup>	590 <sup>(?)</sup>	1780
DTE226	2200	600	2184	592	2015	440	390	1980
DTE228	2200	800	2184	792	2015	640	590	1980
DTE22A	2200	1000	2184	992	2015	840	790	1980
DTE22C	2200	1200	2184	592 <sup>(?)</sup>	2015	440 <sup>(?)</sup>	390 <sup>(?)</sup>	1980