



TTK – IP65 blind floor

Description: To obtain a greater degree of protection on the bottom of the cabinet it is possible to install a painted sheet metal panel at the base of the structure to completely prevent the entry of external agents coming from the floor or from below. The inside gasket adheres perfectly to the frame currents, further isolating the interior of the cabinet. This arrangement ensures that the degree of protection for IP65 cabinets is maintained.

CODE	Nominal dimensions		Other dimensions		
	L	P	L1	L2	L3
TTK404	400	400	170	303	152
TTK405	400	500	170	403	152
TTK406	400	600	170	503	152
TTK408	400	800	170	703	152
TTK40A	400	1000	170	903	152
TTK604	600	400	370	303	352
TTK605	600	500	370	403	352
TTK606	600	600	370	503	352
TTK608	600	800	370	703	352
TTK60A	600	1000	370	903	352
TTK804	800	400	570	303	552
TTK805	800	500	570	403	552
TTK806	800	600	570	503	552
TTK808	800	800	570	703	552
TTK80A	800	1000	570	903	552
TTK104	1000	400	770	303	752
TTK105	1000	500	770	403	752
TTK106	1000	600	770	503	752
TTK108	1000	800	770	703	752
TTK10A	1000	1000	770	903	752
TTK124	1200	400	970	303	952
TTK125	1200	500	970	403	952
TTK126	1200	600	970	503	952
TTK128	1200	800	970	703	952
TTK12A	1200	1000	970	903	952
TTK144	1400	400	1170	303	1152
TTK145	1400	500	1170	403	1152
TTK146	1400	600	1170	503	1152
TTK148	1400	800	1170	703	1152
TTK14A	1400	1000	1170	903	1152