


▶ ROUND SHAPE NAKED TERMINAL


MAXIMUM ELECTRIC CURRENT:
 22-16A.W.G.:19AMPERE 16-14A.W.G.:27AMPERE
 INSULATION MATERIAL:VINYL
 INSULATION COLOR:
 22-16A.W.G.:RED 16-14A.W.G.:BLUE
 TERMINAL MATERIAL:COPPER



WIRE RANGE A. W. G. mm ²	ITEM NUMBER	φ	DIMENSION							CRIMPING TOOL			
			B	F	L	E	D	C	T				
22-16A. W. G. 0.5-1.5mm ²	RV1-3.2	#4	.126 3.2	.216 5.5	.197 5.0	.689 17.5	.394 10.0	.157 4.0	.067 1.7	.030 .075	IZUMI MODEL34 WITH DIE INDEX COLOR:RED OR K. V. MODEL FXT2000A HR1-126 WITH DIE INDEX COLOR:RED		
	RVS1-3.7	#6	.146 3.7	.216 5.5	.197 5.0	.689 17.5	.394 10.0	.157 4.0	.067 1.7	.030 .075			
	RVM1-3.7	#6	.146 3.7	.260 6.6	.248 6.3	.764 19.4	.394 10.0	.157 4.0	.067 1.7	.030 .075			
	RVL1-3.7	#6	.146 3.7	.315 8.0	.276 7.0	.819 20.8	.394 10.0	.157 4.0	.067 1.7	.030 .075			
	RVS1-4	#8	.169 4.3	.260 6.6	.248 6.3	.764 19.4	.394 10.0	.157 4.0	.067 1.7	.030 .075			
	RVL1-4	#8	.169 4.3	.315 8.0	.276 7.0	.819 20.8	.394 10.0	.157 4.0	.067 1.7	.030 .075			
	RV1-5	#10	.209 5.3	.315 8.0	.276 7.0	.819 20.8	.394 10.0	.157 4.0	.067 1.7	.030 .075			
	RVL1-5	#10	.209 5.3	.457 11.6	.433 11.0	1.055 26.8	.394 10.0	.157 4.0	.067 1.7	.030 .075			
	RV1-6	1/4	.252 6.4	.457 11.6	.433 11.0	1.055 26.8	.394 10.0	.157 4.0	.067 1.7	.030 .075			
	RV1-8	5/16	.331 8.4	.457 11.6	.433 11.0	1.055 26.8	.394 10.0	.157 4.0	.067 1.7	.030 .075			
	RV1-10	3/8	.413 10.5	.535 13.6	.547 13.9	1.201 30.5	.394 10.0	.157 4.0	.067 1.7	.030 .075			
	RV1-12	1/2	.512 13.0	.756 19.2	.630 16.0	1.394 35.4	.394 10.0	.157 4.0	.067 1.7	.030 .075			
	RV1-14	9/16	.591 15.0	1.063 27.0	.827 21.0	1.744 44.3	.394 10.0	.157 4.0	.067 1.7	.031 0.8			
	RV1-16	5/8	.669 17.0	1.063 27.0	.827 21.0	1.744 44.3	.394 10.0	.157 4.0	.067 1.7	.031 0.8			
	RV1-20	3/4	.827 21.0	1.063 27.0	.827 21.0	1.744 44.3	.394 10.0	.157 4.0	.067 1.7	.031 0.8			
	16-14A. W. G. 1.5-2.5mm ²	RV2-3.2	#4	.126 3.2	.260 6.6	.189 4.8	.701 17.8	.394 10.0	.177 4.5	.091 2.3		.031 0.8	IZUMI MODEL34 WITH DIE INDEX COLOR:BLUE OR K. V. MODEL FXT2000A HR1-126 WITH DIE INDEX COLOR:BLUE
		RVS2-3.7	#6	.146 3.7	.260 6.6	.189 4.8	.701 17.8	.394 10.0	.177 4.5	.091 2.3		.031 0.8	
		RVM2-3.7	#6	.146 3.7	.260 6.6	.248 6.3	.764 19.4	.394 10.0	.177 4.5	.091 2.3		.031 0.8	
RVL2-3.7		#6	.146 3.7	.335 8.5	.307 7.8	.858 21.8	.394 10.0	.177 4.5	.091 2.3	.031 0.8			
RVS2-4		#8	.169 4.3	.260 6.6	.248 6.3	.764 19.4	.394 10.0	.177 4.5	.091 2.3	.031 0.8			
RVL2-4		#8	.169 4.3	.335 8.5	.307 7.8	.858 21.8	.394 10.0	.177 4.5	.091 2.3	.031 0.8			
RVS2-5		#10	.209 5.3	.335 8.5	.307 7.8	.858 21.8	.394 10.0	.177 4.5	.091 2.3	.031 0.8			
RVL2-5		#10	.209 5.3	.374 9.5	.287 7.3	.858 21.8	.394 10.0	.177 4.5	.091 2.3	.031 0.8			
RV2-6		1/4	.252 6.4	.472 12.0	.433 11.0	1.055 26.8	.394 10.0	.177 4.5	.091 2.3	.031 0.8			

▶ ROUND SHAPE NAKED TERMINAL

MAXIMUM ELECTRIC CURRENT:
 16-14A.W.G:27AMPERE 14-12A.W.G:37AMPERE
 12-10A.W.G:48AMPERE
 MAXIMUM ELECTRICAL RATING:75°C 600 VOLTS MAX.
 INSULATION MATERIAL:VINYL
 INSULATION COLOR
 16-14A.W.G:BLUE 14-12A.W.G:BLACK 12-10A.W.G:YELLOW
 TERMINAL MATERIAL:COPPER



WIRE RANGE A. W. G. mm ²	ITEM NUMBER	φ	DIMENSION INCH MM								CRIMPING TOOL
			B	F	L	E	D	C	T		
16-14A. W. G 1.5-2.5mm ²	RV2-8	5/16	.331 8.4	.472 12.0	.433 11.0	1.055 26.8	.394 10.0	.177 4.5	.091 2.3	.031 0.8	IZUMI MODEL34 WITH DIE INDEX COLOR:BLUE OR K. V. MODEL FXT2000A HRI-126 WITH DIE INDEX COLOR:BLUE
	RV2-10	3/8	.413 10.5	.535 13.6	.547 13.9	1.201 30.5	.394 10.0	.177 4.5	.091 2.3	.031 0.8	
	RV2-12	1/2	.512 13.0	.756 19.2	.630 16.0	1.394 35.4	.394 10.0	.177 4.5	.091 2.3	.031 0.8	
	RV2-14	9/16	.591 15.0	1.063 27.0	.827 21.0	1.744 44.3	.394 10.0	.177 4.5	.091 2.3	.031 0.8	
	RV2-16	5/8	.669 17.0	1.063 27.0	.827 21.0	1.744 44.3	.394 10.0	.177 4.5	.091 2.3	.031 0.8	
	RV2-20	3/4	.827 21.0	1.063 27.0	.827 21.0	1.744 44.3	.394 10.0	.177 4.5	.091 2.3	.031 0.8	
14-12A. W. G 2.5-4mm ²	RV3-4	#8	.169 4.3	.315 8.0	.303 7.7	.984 25.0	.512 13.0	.248 6.3	.188 3.0	.039 1.0	IZUMI MODE214 WITH DIE INDEX COLOR:YELLOW OR K. V. MODEL FXT2000A HRI-126 WITH DIE INDEX COLOR:YELLOW
	RVS3-5	#10	.209 5.3	.315 8.0	.303 7.7	.984 25.0	.512 13.0	.248 6.3	.188 3.0	.039 1.0	
	RVL3-5	#10	.209 5.3	.472 12.0	.370 9.4	1.181 28.4	.512 13.0	.248 6.3	.188 3.0	.039 1.0	
	RV3-6	1/4	.252 6.4	.472 12.0	.370 9.4	1.181 28.4	.512 13.0	.248 6.3	.188 3.0	.039 1.0	IZUMI MODE5 WITH DIE INDEX COLOR:YELLOW OR K. V. MODEL FXT2000A HRI-126 WITH DIE INDEX COLOR:YELLOW
	RV5-3.7	#6	.146 3.7	.283 7.2	.240 6.1	.894 22.7	.512 13.0	.248 6.3	.134 3.4	.039 1.0	
	RVS5-4	#8	.169 4.3	.283 7.2	.240 6.1	.894 22.7	.512 13.0	.248 6.3	.134 3.4	.039 1.0	
	RVL5-4	#8	.169 4.3	.374 9.5	.358 9.1	1.047 26.6	.512 13.0	.248 6.3	.134 3.4	.039 1.0	
	RV5-5	#10	.209 5.3	.374 9.5	.358 9.1	1.047 26.6	.512 13.0	.248 6.3	.134 3.4	.039 1.0	
	RV5-6	1/4	.252 6.4	.472 12.0	.413 10.5	1.167 29.5	.512 13.0	.248 6.3	.134 3.4	.039 1.0	
	RVM5-6	1/4	.252 6.4	.472 12.0	.512 13.0	1.260 32.0	.512 13.0	.248 6.3	.134 3.4	.039 1.0	
	RV5-8	5/16	.331 8.4	.591 15.0	.531 13.5	1.339 34.0	.512 13.0	.248 6.3	.134 3.4	.039 1.0	
	RV5-10	3/8	.413 10.5	.591 15.0	.531 13.5	1.339 34.0	.512 13.0	.248 6.3	.134 3.4	.039 1.0	
RV5-12	1/2	.512 13.0	.756 19.2	.630 16.0	1.520 38.6	.512 13.0	.248 6.3	.134 3.4	.039 1.0		
RV5-14	9/16	.591 15.0	1.260 32.0	.992 25.2	2.134 54.2	.512 13.0	.248 6.3	.134 3.4	.039 1.0		
RV5-16	5/8	.669 17.0	1.260 32.0	.992 25.2	2.134 54.2	.512 13.0	.248 6.3	.134 3.4	.039 1.0		
RV5-20	3/4	.827 21.0	1.260 32.0	.992 25.2	2.134 54.2	.512 13.0	.248 6.3	.134 3.4	.039 1.0		