


## ▶ FORK SHAPE PREINSULATION TERMINAL


MAXIMUM ELECTRIC CURRENT:  
 14-12A.W.G:37AMPERE 12-10A.W.G:48AMPERE  
 MAXIMUM ELECTRICAL RATING:75°C 300 VOLTS MAX.  
 INSULATION MATERIAL:VINYL  
 INSULATION COLOR:  
 14-12A.W.G:BLACK — 12-10A.W.G:YELLOW —  
 TERMINAL MATERIAL:COPPER



WIRE RANGE A. W. G. mm <sup>2</sup>	ITEM NUMBER	φ	DIMENSION INCH									CRIMPING TOOL
			B	F	L	E	D	C	T	mm		
14-12A. W. G. 2.5-4mm <sup>2</sup>	SV3-3.7	#6	.146 3.7	.315 8.0	.276 7.0	.996 25.3	.512 13.0	.248 6.3	.188 3.0	.039 1.0	IZUMI MODEL214 WITH DIE INDEX COLOR:YELLOW OR K. V. MODEL FXT2000A HRI-126 WITH DIE INDEX COLOR:YELLOW	
	SV3-4	#8	.169 4.3	.315 8.0	.276 7.0	.996 25.3	.512 13.0	.248 6.3	.188 3.0	.039 1.0		
	SV3-5	#10	.209 5.3	.315 8.0	.276 7.0	.996 25.3	.512 13.0	.248 6.3	.188 3.0	.039 1.0		
	SV3-6	1/4	.252 6.4	.472 12.0	.358 9.1	1.122 28.5	.512 13.0	.248 6.3	.188 3.0	.039 1.0		
12-10A. W. G 4-6mm <sup>2</sup>	SVS5-3.7	#6	.146 3.7	.283 7.2	.295 7.5	.961 24.4	.512 13.0	.248 6.3	.188 3.0	.039 1.0		IZUMI MODEL 5 WITH DIE INDEX COLOR:YELLOW OR K. V. MODEL FXT2000A HRI-126 WITH DIE INDEX COLOR:YELLOW
	SV5-3.7	#6	.146 3.7	.327 8.3	.276 7.0	1.004 25.5	.512 13.0	.248 6.3	.188 3.0	.039 1.0		
	SVSS5-4	#8	.169 4.3	.283 7.2	.295 7.5	.961 24.4	.512 13.0	.248 6.3	.188 3.0	.039 1.0		
	SVS5-4	#8	.169 4.3	.327 8.3	.276 7.0	1.004 25.5	.512 13.0	.248 6.3	.134 3.4	.039 1.0		
	SVL5-4	#8	.169 4.3	.283 7.2	.276 7.0	1.004 25.5	.512 13.0	.248 6.3	.134 3.4	.039 1.0		
	SV5-5	#10	.209 5.3	.283 7.2	.276 7.0	1.004 25.5	.512 13.0	.248 6.3	.134 3.4	.039 1.0		
	SVS5-6	1/4	.252 6.4	.283 7.2	.276 7.0	1.004 25.5	.512 13.0	.248 6.3	.134 3.4	.039 1.0		
	SVL5-6	1/4	.252 6.4	.472 12.0	.472 12.0	1.240 31.5	.512 13.0	.248 6.3	.134 3.4	.039 1.0		
SV5-8	5/16	.315 8.4	.551 14.0	.413 10.5	1.201 30.5	.512 13.0	.248 6.3	.134 3.4	.039 1.0			

## ▶ FORK SHAPE PREINSULATION TERMINAL

MAXIMUM ELECTRIC CURRENT:  
 22-16A.W.G.:19AMPERE 16-14A.W.G.:27AMPERE  
 MAXIMUM ELECTRICAL RATING:75°C 600 VOLTS MAX.  
 INSULATION MATERIAL:VINYL  
 INSULATION COLOR:  
 22-16A.W.G.:RED — 16-14A.W.G.:BLUE —  
 TERMINAL MATERIAL:COPPER



WIRE RANGE A. W. G. mm <sup>2</sup>	ITEM NUMBER	φ	DIMENSION INCH							CRIMPING TOOL	
			B	F	L	E	D	C	T		
22-16A. W. G. 0.5-1.5mm <sup>2</sup>	SV1-3.2	#4	.126	.323	.256	.827	.394	.157	.067	.030	IZUMI MODEL34 WITH DIE INDEX COLOR: RED OR K. V. MODEL FXT2000A HR1-126 WITH DIE INDEX COLOR: RED
			3.2	5.7	6.5	21.0	10.0	4.0	1.7	.075	
	SVS1-3.7	#6	.146	.323	.256	.827	.394	.157	.067	.030	
			3.7	5.7	6.5	21.0	10.0	4.0	1.7	.075	
	SVL1-3.7	#6	.146	.252	.256	.827	.394	.157	.067	.030	
			3.7	6.4	6.5	21.0	10.0	4.0	1.7	.075	
	SVLL1-3.7	#6	.146	.283	.256	.827	.394	.157	.067	.030	
			3.7	7.2	6.5	21.0	10.0	4.0	1.7	.075	
	SVS1-4	#8	.169	.252	.256	.827	.394	.157	.067	.030	
			4.3	6.4	6.5	21.0	10.0	4.0	1.7	.075	
	SVM1-4	#8	.169	.283	.256	.827	.394	.157	.067	.030	
			4.3	7.2	6.5	21.0	10.0	4.0	1.7	.075	
SVL1-4	#8	.169	.319	.256	.827	.394	.157	.067	.030		
		4.3	8.1	6.5	21.0	10.0	4.0	1.7	.075		
SVS1-5	#10	.209	.319	.256	.827	.394	.157	.067	.030		
		5.3	8.1	6.5	21.0	10.0	4.0	1.7	.075		
SVL1-5	#10	.209	.374	.256	.827	.394	.157	.067	.030		
		5.3	9.5	6.5	21.0	10.0	4.0	1.7	.075		
SVS1-6	1/4	.252	.374	.256	.827	.394	.157	.067	.030		
		6.4	9.5	6.5	21.0	10.0	4.0	1.7	.075		
SVL1-6	1/4	.252	.472	.433	1.063	.394	.157	.067	.030		
		6.4	12.0	11.0	27.0	10.0	4.0	1.7	.075		
16-14A. W. G. 1.5-2.5mm <sup>2</sup>	SV2-3.2	#4	.126	.224	.256	.827	.394	.177	.091	.031	IZUMI MODEL34 WITH DIE INDEX COLOR: BLUE OR K. V. MODEL FXT2000A HR1-126 WITH DIE INDEX COLOR: BLUE
			3.2	5.7	6.5	21.0	10.0	4.5	2.3	0.8	
	SVS2-3.7	#6	.146	.224	.256	.827	.394	.177	.091	.031	
			3.7	5.7	6.5	21.0	10.0	4.5	2.3	0.8	
	SVL2-3.7	#6	.146	.236	.256	.827	.394	.177	.091	.031	
			3.7	6.0	6.5	21.0	10.0	4.5	2.3	0.8	
	SVLL2-3.7	#6	.146	.283	.256	.827	.394	.177	.091	.031	
			3.7	7.2	6.5	21.0	10.0	4.5	2.3	0.8	
	SVS2-4	#8	.169	.252	.256	.827	.394	.177	.091	.031	
			4.3	6.4	6.5	21.0	10.0	4.5	2.3	0.8	
	SVM2-4	#8	.169	.283	.256	.827	.394	.177	.091	.031	
			4.3	7.2	6.5	21.0	10.0	4.5	2.3	0.8	
SVL2-4	#8	.169	.311	.256	.827	.394	.177	.091	.031		
		4.3	7.9	6.5	21.0	10.0	4.5	2.3	0.8		
SVS2-5	#10	.209	.311	.256	.827	.394	.177	.091	.031		
		5.3	7.9	6.5	21.0	10.0	4.5	2.3	0.8		
SVL2-5	#10	.209	3.66	.256	.827	.394	.177	.091	.031		
		5.3	9.3	6.5	21.0	10.0	4.5	2.3	0.8		
SVS2-6	1/4	.252	3.66	.256	.827	.394	.177	.091	.031		
		6.4	9.3	6.5	21.0	10.0	4.5	2.3	0.8		
SVL2-6	1/4	.252	.472	.433	1.063	.394	.177	.091	.031		
		6.4	12.0	11.0	27.0	10.0	4.5	2.3	0.8		