



DBE single door



DBE double blind doors

## ENCLOSURES SERIES OK/AF/AS DBE - Blind door

**Description** the DBE doors are used on the OK series, as well as on the monoblock enclosures series AS and AF. They are made up of metal steel sheet thick 2.0 mm, the supply includes 4 hinges allowing 120° opening and are symmetrical, so the door is fully reversible. The two-component polyurethane gasket is foamed on an external perimeter respect to the locking system, in compliance with IP55 degree of protection. DBE doors include also an inner stiffening frame completely galvanised. The standard locking system is espanolette, 3 mm double bar type.

### DBE code includes:

- Blind door painted RAL 7035 textured, with inner stiffening frame with zama corner pieces
- Set of 4 standard hinges 120° code CAP120 (page 178)
- Set of 4 latches code NTL999 (pag. 177)
- Standard locking, espanolette system, double bar 3mm
- Set of screws and gaskets

**On request: Available hinges 180° opening**

### DBE double blind doors

CODE	Nominal dimensions		Other dimensions			
	H	L	C	D	E	F
DBE1682	1600	800	1584	392 <sup>(2)</sup>	1415	240 <sup>(2)</sup>
DBE1882	1800	800	1784	392 <sup>(2)</sup>	1615	240 <sup>(2)</sup>
DBE2082	2000	800	1984	392 <sup>(2)</sup>	1815	240 <sup>(2)</sup>
DBE2282	2200	800	2184	392 <sup>(2)</sup>	2015	240 <sup>(2)</sup>
DBE18A2	1800	1000	1784	492 <sup>(2)</sup>	1615	340 <sup>(2)</sup>
DBE20A2	2000	1000	1984	492 <sup>(2)</sup>	1815	340 <sup>(2)</sup>
DBE22A2	2200	1000	2184	492 <sup>(2)</sup>	2015	340 <sup>(2)</sup>

(2) Suffix indicating pairs of doors

CODE	Nominal dimensions		Other dimensions			
	H	L	C	D	E	F
DBE126	1200	600	1184	592	1015	440
DBE128	1200	800	1184	792	1015	640
DBE12A	1200	1000	1184	992	1015	340 <sup>(2)</sup>
DBE12C	1200	1200	1184	592 <sup>(2)</sup>	1015	440 <sup>(2)</sup>
DBE146	1400	600	1384	592	1215	440
DBE148	1400	800	1384	792	1215	640
DBE14A	1400	1000	1384	992	1215	340 <sup>(2)</sup>
DBE14C	1400	1200	1384	592 <sup>(2)</sup>	1215	440 <sup>(2)</sup>
DBE166	1600	600	1584	592	1415	440
DBE168	1600	800	1584	792	1415	640
DBE16A	1600	1000	1584	992	1415	340 <sup>(2)</sup>
DBE16C	1600	1200	1584	592 <sup>(2)</sup>	1415	440 <sup>(2)</sup>
DBE184	1800	400	1784	392	1615	240
DBE186	1800	600	1784	592	1615	440
DBE188	1800	800	1784	792	1615	640
DBE18A	1800	1000	1784	992	1615	340 <sup>(2)</sup>
DBE18C	1800	1200	1784	592 <sup>(2)</sup>	1615	440 <sup>(2)</sup>
DBE18D	1800	1400	1784	692 <sup>(2)</sup>	1615	540 <sup>(2)</sup>
DBE18E	1800	1600	1784	792 <sup>(2)</sup>	1615	640 <sup>(2)</sup>
DBE204	2000	400	1984	392	1815	240
DBE206	2000	600	1984	592	1815	440
DBE208	2000	800	1984	792	1815	640
DBE20A	2000	1000	1984	992	1815	340 <sup>(2)</sup>
DBE20C	2000	1200	1984	592 <sup>(2)</sup>	1815	440 <sup>(2)</sup>
DBE20D	2000	1400	1984	692 <sup>(2)</sup>	1815	540 <sup>(2)</sup>
DBE20E	2000	1600	1984	792 <sup>(2)</sup>	1815	640 <sup>(2)</sup>
DBE226	2200	600	2184	592	2015	440
DBE228	2200	800	2184	792	2015	640
DBE22A	2200	1000	2184	992	2015	340 <sup>(2)</sup>
DBE22C	2200	1200	2184	592 <sup>(2)</sup>	2015	440 <sup>(2)</sup>
DBE22D	2200	1400	2184	692 <sup>(2)</sup>	2015	540 <sup>(2)</sup>
DBE22E	2200	1600	2184	792 <sup>(2)</sup>	2015	640 <sup>(2)</sup>

**Note:** - standard opening of the doors is from the right side  
- doors H=1200 and 1400 are available for enclosures AF and AS series